

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-047.0-01

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building
equipment and industrial installations**
(details cf. annex)

Placed on the market under the name or trade mark of

Rockwool A/S

Hovedgaden 501
DK-2640 Hedehusene
Denmark

and produced in the manufacturing plant

Rockwool A/S

Industrivej 9-11
DK-6850 Vamdrup
Denmark

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 30.10.2020 and will remain valid (but no longer than 30.10.2021) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 30.10.2020



Certification Body

Ralph Alberti

Dipl.-Ing. Ralph Alberti

Factory: Rockwool A/S, Industrivej 9-11, DK-6850 Vamdrup, Denmark

Construction product(s): Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations for uses subject to regulations on reaction to fire A2 and A2L. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

Level(s) or class(es) reaction to fire:

Attestation of conformity system: 1

Product			Reaction to fire EN 13501-1				
No.	Form	Name	Description	Classification	Range	Fire Group	Classification report
1	Pipe insulation hanging system	TECLIT Hanger	Pipe insulation hanging system consisting of the following components: - Round core made of mineral wool - Pressure sensitive hotmelt glue - aluminium composite laminate - galvanized steel pipe clamp	A2-s1, d0	Outside diameter: ≤ 300 mm Wall thickness: ≥ 20 mm Density: 194 kg/m³ Mass of organic content: max. 8,7 kg/m³	1	20096J
2	Pipe insulation hanging system	TECLIT Hanger	Pipe insulation hanging system consisting of the following components: - Round core made of mineral wool - Pressure sensitive hotmelt glue - aluminium composite laminate - galvanized steel pipe clamp	A2-s1, d0	Outside diameter: > 300 mm Wall thickness: 30 mm - 120 mm Density: 260 kg/m³ Mass of organic content: max. 11,7 kg/m³	2	20096J

Detail information about the insulation products are given in the classification reports
 Gräfelfing 30.10.2020



Ralph Alberti

Dipl.-Ing. Ralph Alberti