

CONTENTS




3 **Roofs**
Flexible waterproof membrane roof system
Concrete flat roof
Single/double skin metal roof
Pitched tile roof, Sandwich panel roof

6 **Other fire proof insulation**
Roof, Ceiling, Sandwich wall,
Attic insulation



1 **Company profile**



4 **Internal structure**
Light steel frame partition
wall system Sandwich
panel partition wall Floor
insulation



2 **External walls**
ETICS with Stone wool slab /lamella
Ventilated facade, Modular curtain
wall Light steel structure wall
insulation, Sand-wich wall



5 **Passive fire protection**
Fire Duct, Curtain wall fire protection,
Fire resistant partition, Fire door

Improve Energy Efficiency
Reduce Carbon Footprint
Ensure Sustainable Development



ROCKWOOL Group

We are the world leading stone wool manufacturer, with innovative products and systems, committed to protecting the environment and improving people's life.

ROCKWOOL Group is a global leader in thermal insulation, providing world-class firesafe and thermal insulation products and solutions for building structures. Our products help secure fire safety and reduce energy consumption of buildings, coupled with excellent performance in sound absorption, noise reduction and indoor comfort. ROCKWOOL provides green solutions for the horticulture industry, special engineered stone wool fiber for the manufacturing industry, as well as effective insulation solutions for refining and processing industries, marine and offshore industries and other areas. We also have acoustic and vibration reduction system for modern infrastructure construction.

ROCKWOOL Group has a major market share in Europe, but we have also actively expanded our market in Russia, North America, India and East Asia, with more production, sales and service activities operating locally. ROCKWOOL Group's global network helps promote our products and systems around the world.

Headquartered in Denmark, ROCKWOOL group is a listed company of NASDAQ OMX Nordic exchange Copenhagen. At present, it has 51 manufacturers around the world, nearly 12,000 employees and a sales network of more than 120 countries and regions around the world. At the level of corporate governance, ROCKWOOL has a perfect organizational structure and decision-making mechanism of listed companies, which are supervised and managed by the group's management, the board of directors and the


general meeting of shareholders respectively, and the audit committee and Remuneration Committee ensure the smooth development of the group's business strategy.

In China, ROCKWOOL provides a wide range of products for building insulation and other industrial areas that cater to different applications. We have more than 20 years of exploration and operation in China. ROCKWOOL stone wool is integrated with several excellent strengths: fire resilience, thermal properties, acoustic capabilities, durability and sustainability etc. Our products can stand the test of time. They protect buildings and people in any environment while reducing the carbon footprint. ROCKWOOL protects the environment and makes our society develop with a more sustainable approach.

ROCKWOOL China has an annual stone wool production capacity of 100,000 tons in Qingyuan and Yangzhou, and subsidiaries located in Beijing, Guangzhou, Hong Kong, Taiwan, Philippines and other major cities at present.

100 Times

Energy saved in the life cycle of building application is 100 times than energy consumption during the production.



Stone Wool External Thermal Insulation Composite System

Stone wool ETICS is the non-load-bearing fire insulation system, with stone wool slabs as its core material which are fixed to the external walls by adhesive, anchor, etc.,. The system consists of stone wool insulation layer, fixation material (adhesives, anchors, etc.), rendering material (glass fiber mesh embedded, etc.) and finishing coat. With high fire-resistance rating, the system also has excellent performance in thermal insulation, as well as durability, safety and reliability.



Features

- Excellent thermal insulation performance, minimize thermal bridges;
- Class A1 non-combustible;
- Non-flammable and no toxic smoke;
- Good air permeability makes external wall "breathe free";
- High tensile strength, good performance in resisting wind pressure, safe and reliable to use;
- Given same or higher strength and safety, the stone wool DD has lower density, which further reduces the weight and structural load with a lower cost;
- High water-repellency, low water absorption rate, good dimensional stability and durability;
- Excellent sound insulation and noise reduction, no corrosion to metal materials and building components;
- Easy to cut and saw;
- Non-toxic fiber, safe to use.



Applications

Stone wool ETICS is suitable for new built and retrofit projects. It can be applied to frame, masonry and other building structures, and non-transparent curtain wall insulation system.

Products

FacadeRock
FacadeRock DD/DD Plus


Product Range

Product code	Thickness (mm)	Length x Width (mm)
FR10	40 - 100	1200 x 600
FR15	40 - 100	1200 x 600
FR-DD	50 - 150	1200,900,600 x 600
FR-DD Plus	50 - 120	1200,900,600 x 600

Note: Please contact local sales representative for products of size not listed in the table.

Stone Wool Lamella External Thermal Insulation Composite System

Stone wool lamella ETICS is a non-load-bearing fire insulation system, with stone wool lamella as its core material which are fixed to the external walls. The system includes insulation layer of stone wool lamella, fixation material (adhesives, anchors, etc.), rendering material (glass fiber mesh embedded, etc.) and finishing coat. With high fire-resistance rating, the system also has excellent performance in thermal insulation, as well as durability, safety and reliability.



Features

- High tensile strength, excellent performance in resisting wind pressure;
- Excellent insulation performance, minimize thermal bridges;
- Class A1 non-combustible;
- Non-flammable and no toxic smoke;
- Excellent air permeability makes external wall system "breathe free";
- High water-repellency, low water absorption rate, good dimensional stability, contributing to its durability;
- No corrosion to metal materials and building components;
- Light weight, easy to cut and saw;
- Non-toxic fiber, safe to use.

Products

RockBarrier (RB-L)

Product Range

Product code	RB-L100	RB-L120
Nominal density (kg/m ³)	100	120
L x W (mm)	1100x150,1100x200	1100x150,1100x200
Thickness (mm)	50-120	50-120

Note: Please contact local sales representative for products of size not listed in the table.

Good insulation, tensile strength with excellent performance in resisting wind pressure

Applications

Stone wool lamella ETICS is suitable for new built and retrofit projects. It can be applied to multiple building structures, such as frame and masonry. Low density and high strength make stone wool lamella especially suit to high-rise buildings. The material can also be used as fire resistant barrier for other external wall insulation systems, to fully improve the fire safety of external walls.

Ventilated Facade insulation System

Ventilated facade insulation system in this brochure refers to non-transparent curtain wall system with stone wool as its insulation material installed between the facade and a solid substrate such as concrete wall or brick wall to which the stone wool is mechanically fixed.

Applications

The system is suitable for both new buildings and energy saving retrofit projects. It can also be applied to multiple building structures, such as frame and masonry.

Products

VentRock 100
VentRock DD


Features

- Excellent thermal insulation properties, contribute to energy saving;
- Class A1 non-combustible, no toxic smoke;
- High tensile strength, suitable for dry hanging system;
- Remarkable air permeability makes the external wall "breath free";
- High water-repellency, low water absorption rate, good dimensional stability, contributing to its durability;
- No corrosion to metal materials and building components;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.


Product Range

Product code	Thickness (mm)	Length x Width (mm)
VR100	50-150	1200 x 600
VR-DD	50-150	1200 x 600


Note: Please contact local sales representative for products of size not listed in the table.



Metal facade insulation system



Stone curtain wall insulation system



Composite panel curtain wall insulation system

Curtain Wall Fire Protection Insulation System

Curtain wall fire protection insulation system refers to the fire resistant insulation which stops fire and smoke from penetrating through construction structures in curtain wall systems. The system can bring curtain walls with good thermal insulation and excellent fire performance.



Features

- Class A1 non-combustible;
- Fire-resistance up to 2 hours;
- No corrosion to metal materials and building components;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.


Products

CurtainRock
RockSafe



Applications

RockSafe series is used to seal any gaps in construction where smoke or fire may penetrate. Common applications include the isolation between building levels in curtain wall application. Curtainrock series is used as an insulation and fire resistance panel on the backpan of spandrel panel of the curtain wall system.



Product Range

Product code	RS Series			CUR Series		Standard
	RS60	RS80	RS110	CUR110	CUR128	
Nominal density (kg/m ³)	60	80	110	110	128	GB/T 19686
Thickness (mm)	135	135	100	50, 75	100	GB/T 5480
LxW (mm)	1200 x 600			1200 x 600		GB/T 5480

Note: Please contact local sales representative for products of size not listed in the table.

Light Steel Structure Insulation System

Light steel structure, often used in commercial and industrial buildings, is introduced to the residential buildings as well in recent years and becomes a promising trend of residential buildings. It has prominent advantage of easy handling and installation, good structural performance, excellent seismic resistant property and high floor area utilization. ThermalRock can be installed in the light steel wall frame, serving as a guardian to ensure fire safety, acoustics and water resistant performance. It is one of the most suitable insulation materials for light steel wall structure.

Applications

Light steel structure is one of important structures encouraged by government for prefabricated buildings, widely seen in commercial, industrial and residential buildings.

Products

ThermalRock S
ROCKWOOL Acoustic DD/DD Plus

Features

- Class A1 non-combustible;
- Low thermal conductivity and good thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment;
- No corrosion to metal materials and building components;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Product Range

ThermalRock S

Thickness (mm)	Length× Width (mm)	Nominal density (kg/m ³)
50, 75, 100	1200 x 600	40 -140

ROCKWOOL Acoustic DD/DD Plus

Product code	Nominal density (kg/m ³)	Thickness (mm)	Length× Width (mm)
ROCKWOOL AS-DD	≤65	50-150	1200 x 600
ROCKWOOL AS-DD Plus	≤100	50-150	1200 x 600

Note: Please contact local sales representative for products of size not listed in the table.



Sandwich Panel Wall

The factory prefabricated stone wool sandwich panel with different surface outlook can be easily installed by fixing mechanically to building substrates or structures. The sandwich panel wall system acts as a building envelop which provides desirable outlook, reliable fire resistant property and durable thermal performance.



Features

- Class A1 non-combustible, no toxic smoke;
- Excellent compressing, stretching and shearing resistance
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Applications

Sandwich panel external wall system is a good option for various commercial, public and industrial buildings, and can act as a fully-functional metal wall. It is also suitable for extension, reconstruction and temporary or mobile buildings. Thickness of stone wool sandwich panel is flexible to meet different requirements of fire and thermal resistance in projects.

Products

ConRock
StrucRock

Product Range

CR Series offers two types of products: L-Series is supplied by pre-cut lamella, S-Series by thick slab for customers with cutting equipment.

Product code	CR-L10.5	CR-L12	CR-L15
Nominal density (kg/m ³)	105	120	150
L×W (mm)	1200×100		
Thickness (mm)	30-200		

Product code	CR-S10.5	CR-S12	CR-S15
Nominal density (kg/m ³)	105	120	150
L×W (mm)	1200×1200, 1200×600		
Thickness (mm)	100	100	100

Note: Products in other size and thickness are available upon client's request.

Steel Deck Flexible Waterproof Membrane Roof

Steel deck flexible waterproof membrane roof is a single skin membrane roof system with stone wool as its insulation material mechanically fixed on to a steel deck.

Applications



The system is an ideal solution for commercial and industrial buildings, especially for new built and retrofit of steel structure roofs.

Products

HardRock;
RoofRock;
TopRock DD/DD Plus;
TopCover.

Features

- Class A1 non-combustible, heat resistant up to 1000°C, effective in preventing the spread of fire with no toxic smoke or gas produced;
- Excellent resistance to point load and compression, able to bear all types of loads;
- Low thermal conductivity, superior thermal insulation;
- Good dimensional stability, no shrinking, bending or deforming over time, applied as the most stable base layer material, protecting waterproof material from any undesirable pressure;
- Given the same compression strength, TPR-DD/DD Plus has a lower density, reducing the structural load while offering a higher point load;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.



Product Range

Product code	Nominal density (kg/m ³)	Thickness (mm)	Length×Width (mm)
RR30	120	40-150	1200 x 600
HR60	160	40-100	1200 x 600
HR80	180	40-100	1200 x 600
TPR-DD	≤150	50-150	1200 x 600
TPR-DD Plus	≤170	50-150	1200 x 600

Note: Please contact local sales representative for products of size not listed in the table.

Concrete Deck Flat Roof

Concrete deck flat roof system refers to the roof system with concrete deck as substrate, stone wool as insulation and flexible membrane or bitumen as waterproof layer on surface.

Applications


The system applies to the construction or retrofit of concrete roofs in civil, commercial and industrial construction. Since concrete roof has a high heat storage capacity, stone wool insulation layer can create a comfortable environment with stable temperature.

Products

HardRock;
RoofRock;
TopRock DD/DD Plus;
TPR TopPlate and TPR Lamel;
TopCover.

Features

- Class A1 non-combustible, no toxic smoke;
- Excellent resistance to point load and compression, able to bear all types of loads, convenient for regular maintenance;
- Low thermal conductivity, superior thermal insulation;
- Good dimensional stability, not subject to different climates;
- Given the same compression strength, TPR-DD/DD Plus has a lower density, higher point load capacity, better protection of the entire roof system, leakage avoided;
- No partition layer needed between waterproof layer and stone wool insulation layer, compatible with various waterproof membranes;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.



Product Range


Product code	Nominal density (kg/m ³)	Thickness (mm)	Length×Width (mm)
RR30	120	40-150	1200 x 600
HR60	160	40-100	1200 x 600
HR80	180	40-100	1200 x 600
TPR-DD	≤150	50-150	1200 x 600
TPR TopPlate	180	40	1200 x 600
TPR Lamel	65	50-300	1200 x 200

Note: a) Please contact local sales representative for products of size not listed in the table.

b) Please contact local sales representative for more details about ROCKWOOL flat roof insulation solution of TPR-L system (TPR TopPlate and TPR Lamel).

Metal Skin Roof

Single-skin and double-skin metal roofs are commonly seen in metal roof systems. In single-skin system, stone wool insulation is paved on an aluminum foil sheet on top of steel mesh which is attached to purlins. The metal roof skin is installed on top of the insulation. Double-skin metal roof is a system with vertical seam or aesthetic corrugated panel on top, stone wool as the insulation layer, and fixed to the profiled steel sheet at the bottom.



Class A1 non-combustible, no toxic smoke;

Applications

Metal skin roof is widely applied to the roof insulation of large public building, factory and warehouse.

Products

ThermalRock S


Features

- Class A1 non-combustible, no toxic smoke;
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability;
- No corrosion to metal materials and building components;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Product range

Thickness (mm)	Length x Width (mm)	Nominal density (kg/m ³)
50,75,100	1200x600	40-140

Note: Please contact local sales representative for products of size not listed in the table.



Pitched Tile Roof

It is a common application in the roofing construction which has a slope ratio of more than 10%. Tile roof system consists of roof substrate, stone wool insulation layer, waterproof liner layer and different types of tiles. The substrate is covered with stone wool insulation layer by adhesive mortar, which can also be installed with angle steel bars to hold the insulation material.

Applications

Tile roof usually has certain slope ratio which makes the design and installation differ from flat roof system. It is commonly found in low-rise and multi-floor residential buildings.

Product range

Thickness (mm)	Length x Width (mm)	Nominal density (kg/m ³)
50,75,100	1200 x 600	40-140


Note: Please contact local sales representative for products of size not listed in the table.

Features

- Class A1 non-combustible, no toxic smoke;
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment;
- No corrosion to metal materials and building components;

Products

ThermalRock S



Sandwich Panel Roof

The prefabricated stone wool sandwich panel, fixed to the purlin with fasteners, makes the whole system a water proof and thermal insulated roof with good mechanical strength. The system integrates thermal insulation with load-bearing, waterproof and aesthetic features, as well as remarkable fire resistance, light weight, high strength and convenience during the construction.



Features

- Class A1 non-combustible, no toxic smoke;
- Excellent compressing, stretching and shearing resistance
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Applications

Stone wool sandwich panel is usually seen in roof systems of clean rooms, cold storage, electronic and industrial factories.

Products

ConRock
StrucRock

Product Range

CR Series offers two types of products: L-Series is supplied by pre-cut panels, S-Series by thick panels for customers with cutting equipment.

Product code	CR-L10.5	CR-L12	CR-L15
Nominal density (kg/m ³)	105	120	150
L×W (mm)	1200×100		
Thickness (mm)	30-200		

Product code	CR-S10.5	CR-S12	CR-S15
Nominal density (kg/m ³)	105	120	150
L×W (mm)	1200×1200,1200×600		
Thickness (mm)	100	100	100

Note: Products in other size and thickness are available upon client's request.

Light Steel Keel Partition Wall System

Light steel keel partition wall system is a non-load-bearing system fixed on the light steel frame by gypsum boards or calcium silicate boards with stone wool filled in between. As a versatile system, it can be used as any non-load-bearing partition walls in the building. Light steel keel partition wall system has been most widely used, with a wide range of excellent features such as light in weight, good sound insulation, fireproof performance, easy construction and eco-friendly.

Applications

Widely used in a variety of internal partition walls, such as offices, shopping centers, cinemas, hotels, entertainment centers, reading areas, bedroom, etc., can create a comfortable and quite indoor environment, but also very suitable for building reconstruction or expansion Transformation and so on.



Products

ThermalRock S
Acoustic DD/DD Plus

Features

- Light in weight, good acoustic property, excellent fire protection, easy construction;
- Class A1 non-combustible;
- Water repellent, moisture avoided;
- High strength, convenient for installation;
- High dimensional stability, even under high temperature of fire;
- Excellent air permeability, no corrosion to metal materials and building components;
- TR-S ECO products have very low TVOC and certified by CleanAir Gold, with higher environmental performance.



Light steel keel partition wall system



Product Range

Product code	Nominal density (kg/m ³)	Thickness (mm)	Length × Width (mm)
ROCKWOOL AS-DD	≤65	50-150	1200 × 600
ROCKWOOL AS-DD Plus	≤100	50-150	1200 × 600

Note: Please contact local sales representative for products of size not listed in the table.

Sandwich Panel Partition Wall

Stone wool sandwich panel is fixed to vertical keel in the process of horizontally installation, fixations on the top and at the bottom part of the panel are required. Additional finishing on sandwich panel is normally not required. The system is featured by fire protection, tidiness, aesthetics, as well as green, easy installation and recycling.



Applications

The sandwich panel acts as a fireproof and noise absorption partition or room division inside commercial, public or industrial buildings. The galva-nized steel sheet on both sides of the sandwich panel makes it an ideal solution for buildings that have high hygiene standard and intactness requirements, such as facilities for food processing, medicine, electronics and chemical industries. Perforated sandwich panel can also be used in industrial and public space where high level of noise reduction is required.

Products

ConRock
StrucRock

Features

- Class A1 non-combustible, no toxic smoke;
- Excellent compressing, stretching and shearing resistance;
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Product Range

CR Series offers two types of products: L Series is supplied by pre-cut panels, S-Series by thick panels for customers with cutting equipment.


Product code	CR-L10.5	CR-L12
Nominal density (kg/m ³)	105	120
L × W (mm)	1200×100	
Thickness (mm)	30-200	

Product code	CR-S10.5	CR-S12
Nominal density (kg/m ³)	105	120
L × W (mm)	1200×1200,1200×600	
Thickness (mm)	100	100

Note: Products in other size and thickness are available upon client's request.

Floor Insulation

Floor insulation refers to the system of laying floating floors on concrete floors or laying floor decoration materials after filling stone wool between wood keels, so as to improve the sound and thermal insulation between floors. Using stone wool as the insulation material can effectively isolate the impact sound and improve the fireproof and thermal insulation performance of the floor.



Applications

It is an ideal solution for the thermal resistance and noise reduction between indoor floor slabs. The class A non-combustible stone wool insulation can also contribute to the fire safety while providing a comfortable work and living indoor environment.

Products

ThermalRock S
ROCKWOOL FloorRock

Features


- Good performance in sound absorption, effective in reducing floor noise;
- Class A1 non-combustible, no toxic smoke;
- Low thermal conductivity, superior thermal insulation;
- Green and environmentally friendly, safe to use.

Insulation system with better performance in sound and thermal insulation

Product Range

Thickness (mm)	Length × Width (mm)	Nominal density (kg/m ³)
15,20,30,50	1200 × 600	40-140

Note: Please contact local sales representative for products of size not listed in the table.



Fire Duct, Fire seal, Fire Door, Fire Segregation

Stone wool or a combination of stone wool and other non-combustible materials is installed in a building to form a passive fire protection system which prevent or slow down the spread of fire within the building.

Applications

Stone wool is widely used to seal holes and openings on walls, as a filling in fire doors, fireproof partitions, fire segregation installations and other building parts with strict fire resistant standard.

Products

ROCKWOOL Conlit H
ROCKWOOL Conlit D

Features




- With special fire-proof reinforced formula, it can resist high temperature above 1000°C and provide excellent fire safety guarantee;
- The unique fire duct system can achieve the standard requirements of various fire-resistant limit, and the installation is easy and quick;
- Class A1 non-combustible, no toxic smoke;
- Remarkable air permeability;
- Excellent thermal insulation;
- No corrosion to metal materials and building components;
- Good acoustic and vibration damping property;
- Non-toxic fiber, safe to use.

Special fire-proof reinforcement formula is adopted to bring excellent fire-proof performance and maintain good fiber structure stability in high temperature environment

Product Range

	Fire Duct	Curtain wall fire protection, Fire resistant partition, Fire door		
Product code	CL-D	CL-H80	CL-H110	CL-H128
Nominal density	65-180	80kg/m ³	110kg/m ³	128kg/m ³
Thickness (mm)	50-100mm			
L × W (mm)	1200mm × 600mm			

Note: Please contact local sales representative for products of size not listed in the table.



Roof, Ceiling, Sandwich wall, Attic insulation

Stone wool is installed inside the roof, ceiling, sandwich wall, attic and other parts of building, providing fire protection, thermal and sound insulation. It is designed to create a better environment for living and working with enhanced fire safety.



Applications

It applies to building structures that requires sound, fire and thermal insulation, e.g. roof, ceiling, sandwich wall and attic.

Products

ThermalRock S
ThermalRock ECO


Features

- Class A1 non-combustible, no toxic smoke;
- Excellent compressing, stretching and shearing resistance;
- Low thermal conductivity, superior thermal insulation;
- Remarkable air permeability, less moisture in the walls and indoor environment;
- Good acoustic and vibration damping property;
- TR-S ECO products have very low TVOC and certified by CleanAir Gold, with higher environmental performance.

Product Range

Thickness (mm)	Length×Width (mm)	Nominal density (kg/m ³)
50, 75, 100	1200 × 600	40-140

Note: Please contact local sales representative for products of size not listed in the table.



A better environment for living and working with enhanced fire safety

ROCKWOOL Projects

Project	Location	Application	Product	Time of delivery
Shanghai Henglong Plaza	Shanghai	Passive re protection	RS	2000
Shenzhen Huawei	Shenzhen	Building insulation	TR	2002
Guangzhou Baiyun International Airport	Guangzhou	Building insulation	TR	2003
Beijing Olympic Village	Beijing	Building insulation	TR	2006
Shanghai World EXPO Village	Shanghai	ETICS	FR	2008
Inner Mongolia Hongyun Cigarette Factory	Ulan Hot	Sandwich panel	SR	2009
Suzhou Xukou Middle School	Suzhou	ETICS	RB	2010
Hysan Place	Hong Kong	Building insulation	TR	2010
CCTV attached building reconstruction	Beijing	Passive re protection	RS	2011
Renji Hospital of Shanghai Jiaotong University School of Medicine	Shanghai	ETICS	FR	2011
Hefei Cigarette Factory of China Tobacco Anhui	Hefei	Sandwich panel	SR	2011
Beijing Institute of Technology	Beijing	ETICS	RB	2012
Shenyang New World International Garden	Shenyang	ETICS	RB	2012
Dalian Initi Factory	Dalian	Flat roof insulation	HR	2013
Mars Food Factory in Beijing	Beijing	Flat roof insulation	HR	2013
Mingle Place Hotel	Hong Kong	Building insulation	TR	2013
Sanya Shanhaitian Hotel	Sanya	Building insulation	TR	2013
Gansu Agricultural University	Lanzhou	ETICS	FR	2014
Guangzhou Benz Logistic Warehouse	Guangzhou	Flat roof insulation	HR	2014
SAIC Volkswagen Engine Factory	Shanghai	Flat roof insulation	HR	2014
China Merchants Securities Tower	Shenzhen	passive re protection	RS	2014
Disney Fantasyland	Shanghai	Building insulation	TR	2014
Oceanwide International Residential District-Songhai Garden	Wuhan	Building insulation	VR	2015
Shenyang New World EXPO	Shenyang	ETICS	FR	2015
Dalin Power Plant	Taiwan	sandwich panel	CR	2015
The City College of Jilin Jianzhu University	Changchun	ETICS	FR	2015
Shanghai JW Marriott Hotel	Shanghai	Building insulation and PFP	TR/RS	2016
Xiamen Zhongshan Hospital	Xiamen	Interior	TR	2017
Guangzhou CTF Finance Centre	Guangzhou	Passive re protection	RS	2015-2017
Dongguan Huawei	Dongguan	Interior	TR-S	2017
Shenzhen Tencent Building of Binhai	Shenzhen	Building insulation and PFP	TR-S/RS	2015-2017
Shenzhen Pingan IFC	Shenzhen	Building insulation and PFP	TR-S/RS	2015-2017
Huawei Suzhou Project	Suzhou	Sandwich panel	CR	2018
Beijing New Airport South Airlines	Beijing	Flat roof insulation	HR	2018
Beijing New Airport South Airlines	Beijing	Building insulation	TR	2018
Sino-German Ecological Park Kindergarten	Qindao	ETICS	FR	2019
Harbin Tianju Lanwan Villa	Harbin	ETICS	FR-DD	2019
Chimelong Marine Science Museum	Zhuhai	Flat roof insulation	RR	2019
Tencent Yizheng Cloud Computing Date Center	Yizheng	Flat roof insulation	HR	2020
Shenyang New World Garden Residential Phase II	Shenyang	ETICS	RB	2020
China Science and Technology University	Hefei	ETICS	TR	2020
Universal Theme Park Section V	Beijing	Flat roof insulation	HR	2020
Beautiful Scenery Residential	Zhengzhou	ETICS	FR	2021
Hanover International School	Xi'an	ETICS	FR-DD	2021
Hangzhou Asian Games Squash Hall	Hangzhou	Building insulation	AR	2021



Baiyun International Conference Centre, Guangzhou



Sofitel Hotel Guangzhou Sunrich, Guangzhou



Shanghai Bund Financial Centre, Shanghai



Nanshan Cultural Centre, Shenzhen




Hysan Place, Hong Kong



University of Hong Kong, Hong Kong



Galaxy SOHO, Beijing



PetroChina Tower, Beijing