

AENOR

Keymark Certificate Thermal insulation



020/003988

AENOR certifies that the organization

ROCKWOOL PENINSULAR, S.A.U.

registered office PI DE CAPARROSO - CR DE ZARAGOZA KM 53,5 31380 CAPARROSO
(Navarra - España)

supplies Mineral wool

in compliance with UNE-EN 13162:2013+A1:2015 (EN 13162:2012+A1:2015)

Trade mark Monorock Multifix

See annex for more information.

Production site PI DE CAPARROSO - CR DE ZARAGOZA KM 53,5 31380 CAPARROSO
(Navarra - España)

Certification scheme In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP 020.09.

First issued on 2021-09-29

Validity date 2026-09-29

Rafael GARCÍA MEIRO
Chief Executive Officer

Original Electronic Certificate

AENOR

Keymark Certificate Thermal insulation

020/003988

Annex to Certificate

Trade mark Monorock Multifix

Thermal conductivity (W/mK)	Thickness (mm)	Thermal resistance (m ² K/W)	Reaction to fire	Designation code
0,039	40	1,00	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	45	1,15	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	50	1,25	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	55	1,40	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	60	1,50	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	65	1,65	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	70	1,75	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	75	1,90	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	80	2,05	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	85	2,15	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	90	2,30	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	95	2,40	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	100	2,55	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	105	2,65	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	110	2,80	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	115	2,90	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	120	3,05	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	125	3,20	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	130	3,30	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	135	3,45	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	140	3,55	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	145	3,70	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	150	3,80	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	155	3,95	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	160	4,10	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	165	4,20	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	170	4,35	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS

First issued on 2021-09-29
Validity date 2026-09-29

Original Electronic Certificate

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.com

Product certification body accredited by ENAC, number 1/C-PR272

AENOR

Keymark Certificate Thermal insulation

020/003988

Annex to Certificate

Thermal conductivity (W/mK)	Thickness (mm)	Thermal resistance (m ² K/W)	Reaction to fire	Designation code
0,039	175	4,45	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS
0,039	180	4,60	A2-s1, d0	MW-EN 13162-T5-DS(70,90)-CS(10/Y)50-PL(5)500-MU1-WL(P)-WS

First issued on 2021-09-29
Validity date 2026-09-29