

Rockfeu 520

Un-faced rigid slab of volcanic stone wool.

Application

Insulation below slabs in contact with the exterior or uninhabitable areas. Mechanically fixed below the slabs.



Technical Properties

Property	Description				Standard
Nominal density (kg/m ³)	120				EN 1602
Thermal conductivity W/(m*K)	0,039				EN 12667
Dimensions (mm)	1200 x 600				
Fire reaction /Euroclass	A1				EN 13501.1
Thermal resistance (m ² K/W)	Thickness (mm)	Thermal resistance (m ² K/W)	Thickness (mm)	Thermal resistance (m ² K/W)	
	30	0.75	60	1.50	
	40	1.00	70	1.75	
	50	1.25	80	2.05	
Thickness tolerance (mm)	T5				EN 823
Dimensional stability at a specific temperature and humidity	DS (70,90)				EN 1604
Water vapour transmission	MU1	(μ = 1)		EN 12086	
Short term water absorption (kg/m ²)	WS	(< 1,0 kg/m ²)		EN 1609	
Long term water absorption by partial immersion (kg/m ²)	WL(P)	(< 3,0 kg/m ²)		EN 12086	

Advantages

- Fast and easy to install.
- Maximum security in case of fire.
- Well-known improvement of the sound and thermal insulation.
- Neither-hydrophilic nor hygroscopic.
- Chemically inert.
- Environmental Product Declaration
- Free of CFC and HCFC, respectful with the environment.
- Low emissions certificate



Apr-22

ROCKWOOL Peninsular S.A.U.
 Ctra. Zaragoza, Km. 53,5 N121.
 31380 Caparrosa, Navarra, Spain
 T (+34)902 430 430
www.rockwool.es