



Centrum stavebního inženýrství a.s. Praha
Centre of Building Construction Engineering Prague
Akreditované zkušební laboratoře, Autorizovaná osoba,
Oznámený subjekt, Certifikační orgán
Accredited Test Laboratories, Authorised Body,
Notified Body, Certification Body
Pražská 16, 102 00 Praha 10



Notified Body 1390

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1390 – CPR – 0102/08/P

In compliance with the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineral wool products ROCKWOOL used for thermal insulation of buildings, sold under the trade marks

(trade marks and type codes according to EN 13 162 are given in the annex to the certificate)

placed on the market by : **ROCKWOOL Polska, Sp. z o.o.**
ul. Kwiatowa 14
66-131 Cigacice, Poland

and produced in the : **Zakład w Małkini**
manufacturing plant **ul. Jana III. Sobieskiego**
07- 320 Małkinia (production line MAL 5,6,7)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13 162:2012+A1:2015

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product.**

This certificate was first issued on 31. 10. 2008 as a certificate pursuant to CPD and will remain valid as long as neither the harmonised standard, the construction product, the AVPC methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Notified Body 1390
Prague, 31. 03. 2017




Ing. Petr Kučera, CSc.
Deputy of Notified Body 1390



Annex to the Certificate of Constancy of Performance 1390-CPR-0102/08/P
The certificate covers the following products of ROCKWOOL Polska, Malkinia factory:

Trade mark	Thermal conductivity W/mK	Reaction to fire	Type code according to EN 13 162	Line
DOMROCK (d=100-200)	0.045	A1	MW-EN 13162-T1-WS-WL(P)-MU1	MAL7
ROCK-ROLL (d=100-200)				
MATA W (d=100-200)				
MEGAROCK (d=100-200)	0.039	A1	MW-EN 13162-T2-WS-WL(P)-MU1	MAL7
ROCKMIN (d=40-200)				MAL5 MAL6 MAL7
MULTIROCK (d=40-200)				
ROCKBATTS (d=40-200)				
STALROCK (d=40-200)				
PLYTA z WELNY MINERALNEJ (d=40-200)				
ROCKBATTS SUPER (d=40-220)				
TOPROCK (d=80-200)	0.034	A1	MW-EN 13162-T2-WS-MU1	MAL5 MAL7
PANELROCK (d=30-200)	0.035	A1	MW-EN 13162-T2-WS-MU1	MAL7
INDUSTRIAL 50 (d=20-200)	0.036	A1	MW-EN 13162-T3-CS(10)0.5-WS- MU1	MAL5 MAL6 MAL7
INDUSTRIAL 60 (d=20-200)				
PANELROCK 80 (d=40-200)				
INDUSTRIAL 80 (d=20-200)	0.036	A1	MW-EN 13162-T3-CS(10)0.5-WS- MU1	MAL5 MAL6 MAL7
VENTI MAX (d=30-79)				MAL7
VENTI MAX (d=80-200)				
WENTIROCK MAX (d=80-200)				
WENTIROCK (d=20-79)	0.037	A1	MW-EN 13162-T4-CS(10)10-TR7.5-WS- MU1	MAL5 MAL6 MAL7
WENTIROCK (d=80-200)	0.037	A1	MW-EN 13162-T4-CS(10)10-TR7.5-WS-AW 0.95- MU1	
FASROCK MAX (d=80-100)	0.039	A1	MW-EN 13162-T4-DS(70,90)-CS(10)10-TR7.5-WS- MU1	MAL6 MAL7
FASROCK MAX (d=110-200)	0.037	A1		
FASROCK XL (d=80-200)	0.042	A2	MW-EN 13162-T5-DS(70,90)-CS(10)40-TR100-WS- MU1	MAL5 MAL6 MAL7
CB ROCK (d=40-200)	0.038	A1	MW-EN 13162-T4-DS(70,90)-TR7,5-PL(5)100-WS-MU1	
SANDWICH BATTS CB (d=80-200)	0.045	A1	MW-EN 13162-T4-CS(10)70-TR120-WS-MU1-SS50	
BLOCZEK PW LAMELLA (d=40-200)	0.045	A1	MW-EN 13162-T5-CS(10)70-TR120-WS-MU1-SS50	
MONROCK MAX (d=40-79)	0.040	A1	MW-EN 13162-T4-DS(70,90)-CS(10)40-TR7.5-PL(5)350-WS-WL(P)-MU1	



Centrum stavebního inženýrství a.s. Praha
Centre of Building Construction Engineering Prague

Akreditované zkušební laboratoře, Autorizovaná osoba,
 Oznámený subjekt, Certifikační orgán
 Accredited Test Laboratories, Authorised Body,
 Notified Body, Certification Body
 Pražská 16, 102 00 Praha 10



Annex to the Certificate of Constancy of Performance 1390-CPR-0102/08/P
The certificate covers the following products of ROCKWOOL Polska, Malkinia factory:

Trade mark	Thermal conductivity W/mK	Reaction to fire	Type code according to EN 13 162	Line
MONROCK MAX (d=80-200)	0.039	A1	MW-EN 13162-T4-DS(70,90)-CS(10)40-TR7.5-PL(5)400-WS-WL(P)-MU1	MAL6 MAL7
ROOFROCK 50 (d=40-50)	0,038	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)50-TR10-PL(5)600-WS-WL(P)-MU1	MAL7
DACHROCK MAX (d=40-79)	0.041	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)50-TR15-PL(5)400-WS-WL(P)-MU1	MAL5 MAL6 MAL7
DACHROCK MAX (d=80-200)	0.040	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)50-TR15-PL(5)500-WS-WL(P)-MU1	MAL6 MAL7
DACHROCK MAX HARD (d=40-79)	0.042	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)70-TR15-PL(5)400-WS-WL(P)-MU1	MAL5 MAL6 MAL7
DACHROCK MAX HARD (d=80-200)	0.042	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)70-TR15-PL(5)500-WS-WL(P)-MU1	MAL6 MAL7
HARDROCK MAX HARDROCK II (d=50-200)	0,040	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)70 ^{*)} -TR10-PL(5)800-WS-WL(P)-MU1 <i>*)for top layer CS(10)90</i>	MAL7
SPODROCK SPODROCK WG (d=20-180)	0.039	A1	MW-EN 13162-T4-DS(70,90)-CS(10)30-TR7.5-PL(5)300-WS-WL(P)-MU1	MAL5 MAL6 MAL7
INDUSTRIAL 120 (d=20-180)	0,039	A1	MW-EN 13162-T4-WS-MU1	MAL5 MAL6 MAL7
STROPROCK (d=20-200)	0.041	A1	MW-EN 13162-T6-CS(10)50-PL(5)400-WS-CP4-MU1	MAL5 MAL6 MAL7
FLOOR BATTS (d=20-200)				
ROCKLIT (d=20-200)	0.042	A1	MW-EN 13162-T4-TR7,5-WS-MU1	MAL5 MAL6 MAL7
DACHROCK(d=20-200)	0.041	A1	MW-EN 13162-T4-DS(70,90)-CS(10)70-TR15-PL(5)450-WS-WL(P)-MU1	MAL6 MAL7
ROOFROCK 80 (d=20-30) WINDROCK (d=20-30)	0.038	A1	MW-EN 13162-T4-DS(70,-)-DS(70,90)-CS(10)80-TR10-PL(5)700-WS-WL(P)-MU1	MAL7
LAMROCK (d=40-200) LAMROCK MAX(d=40-200)	0.045	A1	MW-EN 13162-T5-DS(70,90)-CS(10)80-TR150-WS-WL(P)-SS70-MU1	MAL7
INDUSTRIAL T 100 (d=15-250)	0,038	A1	MW-EN 13162-T4-CS(10)0,5-WS-MU1	MAL5 MAL6 MAL7
INDUSTRIAL T 120 (d=15-250)	0,038	A1	MW-EN 13162-T4-CS(10)0,5-WS-MU1	
INDUSTRIAL D 110 (d=15-200)	0.038	A1	MW-EN 13162-T4-WS-MU1	MAL5 MAL6 MAL7
INDUSTRIAL D 190 (d=15-200)	0.045	A1	MW-EN 13162-T4-WS-MU1	MAL6 MAL7
BETAROCK 80 (d=15-200)	0.038	A1	MW-EN 13162-T4 -WS-MU1	MAL5 MAL6 MAL7
BETAROCK 110 (d=15-200)	0.038	A1	MW-EN 13162-T4-WS-MU1	
BETAROCK 150 (d=15-200)	0.040	A1	MW-EN 13162-T4-WS-MU1	



Centrum stavebního inženýrství a.s. Praha
Centre of Building Construction Engineering Prague

Akreditované zkušební laboratoře, Autorizovaná osoba,
Oznámený subjekt, Certifikační orgán
Accredited Test Laboratories, Authorised Body,
Notified Body, Certification Body
Pražská 16, 102 00 Praha 10



Annex to the Certificate of Constancy of Performance 1390-CPR-0102/08/P
The certificate covers the following products of ROCKWOOL Polska, Malkinia factory:

Trade mark	Thermal conductivity W/mK	Reaction to fire	Type code according to EN 13 162	Line
BETAROCK 180 (d=15-200)	0,045	A1	MW-EN 13162-T4-WS-MU1	MAL6
MARC 180 (d=15-150)	0,045	A1	MW-EN 13162-T4-WS-MU1	MAL7
FIRE DOORS D 110 (d=15-150)	0,038	A1	MW-EN 13162-T4 -WS-MU1	MAL5
FIRE DOORS D 150 (d=15-150)	0,040	A1	MW-EN 13162-T4 -WS-MU1	MAL6 MAL7
FIRE DOORS D 190 (d=15-150)	0,045	A1	MW-EN 13162-T4-WS-MU1	MAL6 MAL7
LAMROCK S (d=40-200)	0,044	A1	MW-EN 13162-T5-TR80	MAL7
LAMROCK M (d=40-200)	0,045	A1	MW-EN 13162-T5-TR100	MAL7
LAMROCK XS (d=40-200)	0,041	A1	MW-EN 13162-T5-TR80	MAL7
SPANROCK L (d=40-240)	0,040	A1	MW-EN 13162-T5-TR5	MAL7
SPANROCK M (d=40-240)	0,038	A1	MW-EN 13162-T5-TR5	MAL7
SPANROCK M-M (d=40-240)	0,038	A1	MW-EN 13162-T5-TR5	MAL7
SPANROCK S (d=40-240)	0,038	A1	MW-EN 13162-T5-TR5	MAL7
SPANROCK XL (d=40-240)	0,040	A1	MW-EN 13162-T5-TR5	MAL7
SPANROCK XS (d=40-240)	0,041	A1	MW-EN 13162-T5-TR5	MAL7



Notified Body 1390
Prague, 31. 03. 2017


Ing. Petr Kučera, CSc.
Deputy of Notified Body 1390