
NBS Specification: ROCKWOOL FIREPRO® Acoustic Intumescent Sealant

PRODUCT SUMMARY:

A high specification, water based acrylic sealant suitable for sealing joints and service penetrations in fire walls, partitions, fire rated door frames and glazing systems.

PRODUCT GENERAL DESCRIPTION:

ROCKWOOL FirePro Acoustic Intumescent Sealant is used to reinstate the fire resistance of wall and floor constructions where apertures are penetrated by multiple services or linear gaps. The product is comprehensively tested, for use with ROCKWOOL Ablative Coated Batt or as a linear joint seal.

FEATURES AND BENEFITS:

- Up to 4 hours fire resistance.
- Air leakage tested.
- Suitable for linear joints up to 50 mm wide.
- Suitable with multiple substrates and services.
- Increased movement capability.
- CE Marked to EAD 350141-00-1106 & EAD 350454-00-1104.

ACOUSTIC PERFORMANCE:

Weighted Sound Reduction Index (Rw) of up to 57dB dependant on:

- Type of construction.
- Type of seal backing.
- Size of joint.

APPLICATION:

Designed for use in the installation of ROCKWOOL Ablative Coated Batt, sealing linear joints and individual service penetrations passing through various substrates.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

ROCKWOOL FIREPRO Acoustic Intumescent Sealant
ROCKWOOL FIREPRO Acoustic Intumescent Sealant - Trowel grade

PRODUCT PROPERTIES:

Standard:

- White
- Grey Non-Standard - subject to minimum order quantity

Size:

- 310mL cartridge
- 600mL foil sausage
- 5L tub

Resistance to fire performance: Up to EI240 when tested to BS EN 1366-3: 2009 and BS EN 1366-4: 2006 +A1:2010

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490

www.rockwool.com/uk/