

---

## NBS Specification: ROCKWOOL FIREPRO® Fire Rated Silicone Sealant

### PRODUCT SUMMARY:

A one part alkoxy cure fire resistant silicone sealant.

### PRODUCT GENERAL DESCRIPTION:

ROCKWOOL Fire Resistant Sealant is a high performance silicone which has been designed for use in joints with high movement capability or where joints are formed between dissimilar substrate types, e.g., steel and masonry. ROCKWOOL Fire Resistant Silicone Sealant is suitable for joints up to 40 mm and can provide up to 4 hours fire resistance.

### FEATURES AND BENEFITS:

- Up to 4 hours fire resistance.
- Sealing joints up to 40 mm.
- Suitable with multiple substrates.
- Suitable in joints with high movement capability.

### APPLICATION:

Application of ROCKWOOL Fire Resistant Silicone Sealant it is a simple process as the product is extruded from a cartridge loaded into a standard sealant gun. The depth of the joint will depend on the gap to be filled and the fire rating required.

### PRODUCT SPECIFICATION CLAUSE

### PRODUCT REFERENCE:

ROCKWOOL FIREPRO Fire Rated Silicone Sealant

### PRODUCT PROPERTIES:

**Size:** 310mL Cartridge

**Standard:** [d] Tested to BS 476-20

**Colour:** [d] White

**Resistance to fire performance:** [d] Up to 4 hours fire resistance

### CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

**Email:** [technical.solutions@rockwool.co.uk](mailto:technical.solutions@rockwool.co.uk)

**Telephone:** 01656 868 490

[www.rockwool.com/uk/](http://www.rockwool.com/uk/)