
NBS Specification: ROCKWOOL FIREPRO® Firestop Compound

PRODUCT SUMMARY:

Fire stopping load bearing compound to provide a fire rated seal.

PRODUCT GENERAL DESCRIPTION:

The installation of ROCKWOOL's Firestop Compound provides up to 6 hours fire protection to provide a fire resisting seal around service penetrations through all fire rated walls and floors. As independent tests have shown, when reinforced, Firestop Compound offers masonry and concrete walls or concrete floors with up to 360 minutes protection for both integrity and insulation, and when un-reinforced, it offers up to 240 minutes protection.

Existing compound installations can be easily drilled to allow the provision of additional or replacement services which can subsequently be re-sealed.

The ROCKWOOL Firestop product is easy to use as it's a specially formulated gypsum based compound, which is mixed with water to be trowelled or poured around service penetrations.

FEATURES AND BENEFITS:

- Smoke seal.
- Suitable for sealing around most types of service.
- Load bearing capability.
- Simple installation.
- No smoke emission.
- Unaffected by humidity.

APPLICATION:

As part of the comprehensive FIREPRO® range of fire protection products, the Firestop Compound is suitable for cable pipe and duct penetrations.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

ROCKWOOL Firepro Firestop Compound

PRODUCT PROPERTIES:

Size: 22kg bags

Fire resistance: [d] Up to 6 hours fire protection

Load bearing capacity: [d] Up to 2.5KN

Acoustic performance: [d] Up to 51dB

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490

www.rockwool.com/uk/